

# PVM220S

21.5" FHD Display with HDMI, 3G-SDI, USB Type-C Interfaces




## 21.5" Live Stream Quad Split Multiview Monitor


Multiview monitor for Android mobile phone, DSLR camera and camcorder. Application for live streaming & multi camera.



# Multi Camera, Multiview Switch

Monitor can be switched live up to 4 1080P high quality video signal inputs, which make it easy to create professional multi camera events for live streaming. At a time when live stream in mobile phone is popular, monitor innovatively built in phone mode so as to directly display a vertical video in multi camera. All-in-one capability greatly reduces the cost of productions.





# PVW / PGM Video SDI, HDMI Output Simultaneously


PGM ports for switching camera video from SDI, HDMI and USB Type-C signals

Multi camera video sources can be set up as Preview source and finished Program source for quick switching source of live streaming to video capture via shortcuts, and finally to Youtube, SKype, Zoom and any more social media platforms.




# Camera Auxiliary Functions

Plenty of auxiliary functions for live streaming and multi camera productions, that assist user grasp the scene details in front of camera more thoroughly, such as light, color, layout and so on.



The figure on left side of screen displays level meter showing audio levels for channels 1 and 2 of the input source.



A display that indicates how many pixels of the screen are at a particular brightness level.



Special colors are used to indicate different levels of brightness in the image. Support ARRI, RED false color.



Adjusts a wide range of aspect marker, safety marker and center marker. It can also weaken the sense of the image outside the marker.



It highlights the areas that are in focus so you are able to quickly focus the camera and not miss crucial shots.




Areas of image over a certain threshold are filled with striped pattern to dramatically highlight areas where too much light is falling on image sensor.



# USB Type-C Input, Vertical Full Screen For Phone

Unique phone mode, adapts to vertical image output from phone camera

Unlike the regular video camera, some phone's video sources are displayed as vertical images. Multiview mode is innovatively blend of horizontal and vertical images layout, making live production more efficient.




# Workflows

Supports up to 4 live video signals, that can use HDMI or SDI outputs for program video. All the live events can also be cut between PVW and PGM, incredibly doing the work as a video switcher.



# Create Professional Programs

Show the world your legendary story through live streaming. Whatever the applications, there will always be a necessary for an innovative multi camera monitor to help with your video production.



## Easy to Use

It built in F1 and F2 shortcut buttons allow you to set a designated function and turn it on and off at one touch.

### DISPLAY

Panel	21.5"
Physical Resolution	1920×1080
Aspect Ratio	16:9
Brightness	500 nit
Contrast	1500:1
Viewing Angle	170°/170° (H/V)

### VIDEO INPUT

SDI × 2	1080p 60/59.94/50/30/29.97/25/24/23.98; 1080i 60/59.94/50; 720p 60/59.94/50 and more signals...
HDMI × 2	1080p 60/59.94/50/30/29.97/25/24/23.98; 1080i 60/59.94/50; 720p 60/59.94/50 and more signals...
USB Type-C × 1	1080p 60/59.94/50/30/29.97/25/24/23.98; 1080i 60/59.94/50; 720p 60/59.94/50 and more signals...

### VIDEO OUTPUT

SDI × 2	1080p 60/59.94/50/30/29.97/25/24/23.98; 1080i 60/59.94/50; 720p 60/59.94/50 and more signals...
PGM HDMI/SDI × 1	1080p 60/50/30/25/24

### AUDIO IN/OUT

SDI	2ch 48kHz 24-bit
HDMI	2ch 24-bit
Ear Jack	3.5mm
Built-in Speakers	1

### POWER

Input Voltage	DC 12-24V
Power Consumption	≤33W (15V)

### ENVIRONMENT

Operating Temperature	-20°C~60°C
Storage Temperature	-30°C~70°C


### OTHERS

Dimension (LWD)	508mm×321mm×47mm
Weight	5.39kg

### STANDARD



### OPTIONAL



[www.lilliput.com](http://www.lilliput.com)

ZHANGZHOU LILLIPUT ELECTRONIC TECHNOLOGY CO., LTD.

Add : Zong Si Road, Lan Tian Economic Development Zone, Zhang Zhou, Fu Jian, 363005, China  
Tel: +86-596-2109661/2109323 Fax: +86-596-2109611 Email: sales@lilliput.com

